



HIGH OUTPUT LAMPS-

High Output (HO) germicidal lamps yield 1/3 to 2/3 more ultraviolet output than standard lamps of the same length. Ballasting is available in 120v and 220v. Custom designed lengths can also be supplied.

The unique single-ended design is suited for test tube-shaped quartz sleeve application. The end of the lamp with the pins is positioned at the open end of the sleeve at the top.

This reduces electrical problems associated with condensation at the bottom of vertical units. Electrical continuity is accomplished through the use of two external Teflon coated wires. Longer lengths employ spacing rings. The 4-pin single ended design permits the use of standard Steadfast[™] sockets. The lamps are supplied with ceramic bases, which are resistant to ultraviolet and ozone. They will not burn or deteriorate, and they eliminate quartz sleeve fogging.



	Base Face Length		Arc Length		1	Current	Voltage	UV Ou 254	tput at nm
Lamp Catalog Number	Inches	mm	Inches	mm	Watts	mA	50/60Hz	Watts	µW/cm2
05-0331 - GPH436T5L/HO/4PSE	17.2	436.0	14.2	360	48	800	70	13	120
05-0332 - GPH436T5/VH/HO/4PSE	17.2	436.0	14.2	360	48	800	70	13	120
05-0264 - GHO36T5/L/4PSE	33.2	842.4	29.7	755	87	800	125	28	260
05-0265 - GHO36T5/VH/4PSE	33.2	842.4	29.7	755	87	800	125	28	260
05-0333 - GPH846T5/L/HO/4PSE	33.3	846.0	30.2	767	90	800	127	29	265
05-0334 - GPH846T5/VH/HO/4PSE	33.3	846.0	30.2	767	90	800	127	29	265
05-0335 - GPH893T5/L/HO/4PSE	35.2	893.0	32.1	815	95	800	135	30	270
05-0336 - GPH893T5/VH/HO/4PSE	35.2	893.0	32.1	815	95	800	135	30	270
05-0337 - GHO64T5/L/4PSE	61.2	1553.6	55.9	1421	155	800	220	45	380
05-0338 - GHO64T5/VH/4PSE	61.2	1553.6	55.9	1421	155	800	220	45	380

(1) At line frequencies (50 or 60Hz) the lamp wattage is not simply the product of the lamp voltage and current. This product must be multiplied by the apparent power factor (approximately 0.8) to determine the true wattage. At high frequency (>10Khz) the power factor is one and the wattage is obtained as the product of voltage and current.

Atlantic Ultraviolet lamps and equipment are manufactured in the USA.

CAUTION: Exposure to direct or reflected germicidal ultraviolet rays will cause painful eye irritation and reddening of the skin. Personnel subject to such exposure must wear suitable faceshield, gloves and protective clothing.

Hg - LAMP CONTAINS MERCURY, manage in accord with disposal laws, see: www.lamprecycle.org.

The information and recommendations contained in this publication are based upon data collected by the Atlantic Ultraviolet Corporation and are believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. Specifications and information are subject to change without notice.

Document No. 98-1149 • Revised February 2007 • ©2003-2007 by Atlantic Ultraviolet Corporation

375 Marcus Boulevard • Hauppauge, NY 11788 631.273.0500 • Fax: 631.273.0771 www.ultraviolet.com e-mail: info@ultraviolet.com

www.ultraviolet.com